

VIGOR

NXT-GEN INDUCTION HEATER



A PRODUCT OF CELETTE

WWW.CELETTE.COM | WWW.CELETTE-USA.COM



UNIQUE BENEFITS:




- Adaptive inductance field reading (autotuning)
- Electronic safety protection
- Heating temperature level setting
- Long inductor cable 4.25 m
- Plug and Play with art. IND11kW/M inductor head

APPLICATIONS:

The CEL.HDi13K230KB heat inductors are ideal for a wide range of applications such as:

- Bolts/nuts releasing
- Pin or bearing release and replacement
- Heating for straightening
- Pre-heating before welding ➤ Bending
- Hardening ➤ Annealing

OPTIONAL ACCESSORIES

 CEL.IND-5 KW/S 04.1  CEL.IND-11KW S04	 CEL.IND-16 KW/V NT.1  CEL.IND-11KW/V NT
 CEL.IND-11KW/U01 - Ø 40 MM	 CEL.IND - 11 KW/V NT.1  CEL.IND-11KW/V NT



550x560x1009h mm



800x850x1350h mm



156 KG



Input power 13 KW - 32 A
Electrical connection IEC60309



230V/3P+T 50Hz



Working frequency 15-30 KHz



8 m Network cable



IP 21 Degree of protection



Main circuit breaker



20lt tank - Liquid cooling system



Hydraulic heat exchanger with fan



UNIQUE BENEFITS:



- Adaptive inductance field reading (autotuning)
- Electronic safety protection
- Heating temperature level setting
- Long inductor cable 4.25 m
- Plug and Play with art. IND11kW/M inductor head

APPLICATIONS:

The CEL.HDi13K400KB heat inductors are ideal for a wide range of applications such as:

- Bolts/nuts releasing
- Pin or bearing release and replacement
- Heating for straightening
- Pre-heating before welding ➤ Bending
- Hardening ➤ Annealing

OPTIONAL ACCESSORIES



550x560x1009h mm



800x850x1350h mm



120 KG



Input power 13 KW - 32 A
Electrical connection IEC60309



400V/3P+T 50Hz



Working frequency 15-30 KHz



8 m Network cable



IP 21 Degree of protection



Main circuit breaker



20lt tank - Liquid cooling system



Hydraulic heat exchanger with fan



UNIQUE BENEFITS:

- Adaptive inductance field reading (autotuning)
- Electronic safety protection
- Heating temperature level setting
- User friendly color touch control panel 5"
- Long inductor cable 4.25 m
- Plug and Play with art. IND11kW/M inductor head

APPLICATIONS:

The CEL.HDi18K400TC heat inductors are ideal for a wide range of applications such as:

- Bolts/nuts releasing
- Pin or bearing release and replacement
- Heating for straightening
- Pre-heating before welding ➤ Bending
- Hardening ➤ Annealing

OPTIONAL ACCESSORIES

 CEL.IND-11KW S04	 CEL.IND-16KW/V	 CEL.IND-11/TT 140 - Ø 140 MM
 CEL.IND-11/TT 110 - Ø 110 MM	 CEL.IND - 16KW/4 - Ø 65 MM	 CEL.IND-16KW/2 - Ø 180 MM
 CEL.IND-16KW/U02 - Ø 68 MM	 CEL.IND-16KW/L	



550x560x1009h mm



800x850x1350h mm



130 KG



Input power 18 KW - 32 A
Electrical connection IEC60309



400V/3P+T 50Hz

FREQ

Working frequency 15-30 Khz



8 m Network cable



IP 21 Degree of protection



Main circuit breaker



20lt tank - Liquid cooling system



Hydraulic heat exchanger with fan

**CELETTE FRANCE S.A.S**

3, AVENUE MARCELLIN BERTHELOT 38200
VIENNE / FRANCE
☎ +33 474 575 959

**CELETTE DEUTSCHLAND GMBH**

EUGEN-ENSSLIN-STR.3 77694 KEHL
GERMANY
☎ +49 785 195 58 712

**CELETTE NORTH AMERICA**

700/122 VALLEY RIDGE BLVD.LEWISVILLE,
TX 75057 / USA
☎ +1 254 382 8698

**CELETTE INDIA PVT LTD.**

2/122 B-1, MYLAMPATTY ROAD,
KARAYAMPALAYAM,
COIMBATORE 641062 / INDIA
☎ +91 88 70 86 11 11

**CELETTE AUTO EQUIPMENT
AND REPARATION**

ROOM 3, 11F, XING HUI BUILDING,
NO 176, MIN YANG ROAD,
JIAXING, 31400 ZHEJIANG PROVINCE / CHINA
☎ +86 158 8831 7667

**CELETTE JAPAN TECHNICAL OFFICE**

667-9 MABASHI, SHISUI-MACHI, INBA-GUN,
CHIBA 285-0914 / JAPAN
☎ +81 70 2183 1960

**CELETTE ASIA PACIFIC**

700/941 M.5 AMATA CITY
CHONBURI INDUSTRIAL ESTATE,
NONGKAKHA, PHANTHONG 20160
CHONBURI / THAILAND
☎ +66 905 630 258

✉ INFO@CELETTE.COM |  WWW.CELETTE.COM

